



190711
REV. 11
THIS DRAWING IS A CONTROLLED DOCUMENT

USED ON




Left Side
 Connector(s): LC-Duplex Secure
 Mode: MM
 Housing Color: Red
 Geom. Spec: N/A

Fiber Path
 A - - Fiber B
 B - - Fiber A

Right Side
 Connector(s): MT-RJ (No Pins)
 Mode: MM
 Housing Color: Black
 Geom. Spec: 115-1215

- Notes:**
- 1 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
 - 2 Includes dust caps (not shown on print).
 - 3 IL tested at 1300nm.
 - 4 Label 2 will not be present on any cable assembly less than 5 meters long.



VIEW D-D
NOT TO SCALE

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS, INC. IT IS THE PROPERTY OF TYCO ELECTRONICS, INC. AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC	CE
DIST	16

A	Rev Per EC#	RELEASE	3/21/2007	-	JD		
P	LTR	REVISION RECORD	DATE	DN	APVD		

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
meters	0 PLC ± .
	1 PLC ± .
	2 PLC ± .
	3 PLC ± .
	4 PLC ± .

Restricted To:

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Joe Davis		
APVD	Joe Davis	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)		
SCALE	SIZE	DRAWING NO	SHEET
NTS	A2	C- 1907114	1 of 4
			REV A

THIS DRAWING IS A CONTROLLED DOCUMENT.

Part #	L (meters)	L (feet)	LC-Duplex Secure, Red		MT-RJ (No Pins), Black	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1907114-1	0.950 - 1.050	3.11 - 3.44	0.5	-	0.5	20
0-1907114-2	1.950 - 2.050	6.39 - 6.72	0.5	-	0.5	20
0-1907114-3	2.950 - 3.050	9.67 - 10.00	0.5	-	0.5	20
0-1907114-4	3.920 - 4.080	12.86 - 13.38	0.51	-	0.51	20
0-1907114-5	4.920 - 5.080	16.14 - 16.66	0.51	-	0.51	20
0-1907114-6	5.920 - 6.080	19.42 - 19.94	0.51	-	0.51	20
0-1907114-7	6.920 - 7.080	22.70 - 23.22	0.51	-	0.51	20
0-1907114-8	7.920 - 8.080	25.98 - 26.50	0.51	-	0.51	20
0-1907114-9	8.850 - 9.150	29.03 - 30.01	0.51	-	0.51	20
1-1907114-0	9.850 - 10.150	32.31 - 33.30	0.52	-	0.52	20
1-1907114-1	10.850 - 11.150	35.59 - 36.58	0.52	-	0.52	20
1-1907114-2	11.850 - 12.150	38.87 - 39.86	0.52	-	0.52	20
1-1907114-3	12.850 - 13.150	42.15 - 43.14	0.52	-	0.52	20
1-1907114-4	13.850 - 14.150	45.43 - 46.42	0.52	-	0.52	20
1-1907114-5	14.850 - 15.150	48.72 - 49.70	0.52	-	0.52	20
1-1907114-6	15.840 - 16.160	51.96 - 53.01	0.52	-	0.52	20
1-1907114-7	16.830 - 17.170	55.21 - 56.33	0.53	-	0.53	20
1-1907114-8	17.820 - 18.180	58.46 - 59.64	0.53	-	0.53	20
1-1907114-9	18.810 - 19.190	61.71 - 62.95	0.53	-	0.53	20
2-1907114-0	19.800 - 20.200	64.96 - 66.27	0.53	-	0.53	20
2-1907114-1	20.790 - 21.210	68.20 - 69.58	0.53	-	0.53	20
2-1907114-2	21.780 - 22.220	71.45 - 72.90	0.53	-	0.53	20
2-1907114-3	22.770 - 23.230	74.70 - 76.21	0.53	-	0.53	20
2-1907114-4	23.760 - 24.240	77.95 - 79.52	0.54	-	0.54	20
2-1907114-5	24.750 - 25.250	81.20 - 82.84	0.54	-	0.54	20
2-1907114-6	25.740 - 26.260	84.44 - 86.15	0.54	-	0.54	20
2-1907114-7	26.730 - 27.270	87.69 - 89.46	0.54	-	0.54	20
2-1907114-8	27.720 - 28.280	90.94 - 92.78	0.54	-	0.54	20
2-1907114-9	28.710 - 29.290	94.19 - 96.09	0.54	-	0.54	20
3-1907114-0	29.700 - 30.300	97.44 - 99.40	0.55	-	0.55	20
3-1907114-1	30.690 - 31.310	100.68 - 102.72	0.55	-	0.55	20
3-1907114-2	31.680 - 32.320	103.93 - 106.03	0.55	-	0.55	20
3-1907114-3	32.670 - 33.330	107.18 - 109.35	0.55	-	0.55	20
3-1907114-4	33.660 - 34.340	110.43 - 112.66	0.55	-	0.55	20
3-1907114-5	34.650 - 35.350	113.68 - 115.97	0.55	-	0.55	20
3-1907114-6	35.640 - 36.360	116.92 - 119.29	0.55	-	0.55	20
3-1907114-7	36.630 - 37.370	120.17 - 122.60	0.56	-	0.56	20
3-1907114-8	37.620 - 38.380	123.42 - 125.91	0.56	-	0.56	20
3-1907114-9	38.610 - 39.390	126.67 - 129.23	0.56	-	0.56	20
4-1907114-0	39.600 - 40.400	129.92 - 132.54	0.56	-	0.56	20
4-1907114-1	40.590 - 41.410	133.16 - 135.85	0.56	-	0.56	20
4-1907114-2	41.580 - 42.420	136.41 - 139.17	0.56	-	0.56	20

Qty	U of M	Description	Item No.
2	piece	Trace Label	14
2	piece	Eyelet/Shrink tube assembly - White	13
1	piece	MT-RJ TwinZip Bend Limiting Boot, Beige	12
1	piece	MT-RJ FERRULE, THERMOPLAST,MM	11
AR	meter	2 fiber, 50/125, 1.8mm, Twinzip, Orange, OFNP (Plenum)	10
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	9
1	piece	LC Duplex clip, black	8
2	piece	LC, SC, FC Straight Boot, Beige	7
1	piece	CRIMP EYELET, MT-RJ	6
1	piece	MT-RJ, SPRING PUSH, UNIVERSAL	5
1	piece	PIN KEEPER, 3.8MM	4
1	piece	SPRING, MT-RJ, 3.8 DESIGN	3
1	piece	DUST COVER, MT-RJ	2
1	piece	HOUSING, CONN, MT-RJ,BLACK	1

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

A	Rev Per EC#	RELEASE	3/21/2007	-	JD		
P	LTR	REVISION RECORD	DATE	DN	APVD		

DIMENSIONS: meters	TOLERANCES UNLESS OTHERWISE SPECIFIED: 9 PLC ± . 1 PLC ± . 2 PLC ± . 3 PLC ± . 4 PLC ± .
-----------------------	---

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Joe Davis		
APVD	Joe Davis	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)		
SCALE	NTS	SIZE	A2
DRAWING NO	C- 1907114		SHEET
			2 of 4
REV	A		

Restricted To:


THIS DRAWING IS A CONTROLLED DOCUMENT. BFC:ND

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS AFFILIATES. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC
CE
DIST
16

Part #	L (meters)	L (feet)	LC-Duplex Secure, Red		MT-RJ (No Pins), Black	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1907114-3	42.570 - 43.430	139.66 - 142.48	0.56	-	0.56	20
4-1907114-4	43.560 - 44.440	142.91 - 145.80	0.57	-	0.57	20
4-1907114-5	44.550 - 45.450	146.16 - 149.11	0.57	-	0.57	20
4-1907114-6	45.540 - 46.460	149.40 - 152.42	0.57	-	0.57	20
4-1907114-7	46.530 - 47.470	152.65 - 155.74	0.57	-	0.57	20
4-1907114-8	47.520 - 48.480	155.90 - 159.05	0.57	-	0.57	20
4-1907114-9	48.510 - 49.490	159.15 - 162.36	0.57	-	0.57	20
5-1907114-0	49.500 - 50.500	162.40 - 165.68	0.58	-	0.58	20
5-1907114-1	50.490 - 51.510	165.64 - 168.99	0.58	-	0.58	20
5-1907114-2	51.480 - 52.520	168.89 - 172.30	0.58	-	0.58	20
5-1907114-3	52.470 - 53.530	172.14 - 175.62	0.58	-	0.58	20
5-1907114-4	53.460 - 54.540	175.39 - 178.93	0.58	-	0.58	20
5-1907114-5	54.450 - 55.550	178.64 - 182.25	0.58	-	0.58	20
5-1907114-6	55.440 - 56.560	181.88 - 185.56	0.58	-	0.58	20
5-1907114-7	56.430 - 57.570	185.13 - 188.87	0.59	-	0.59	20
5-1907114-8	57.420 - 58.580	188.38 - 192.19	0.59	-	0.59	20
5-1907114-9	58.410 - 59.590	191.63 - 195.50	0.59	-	0.59	20
6-1907114-0	59.400 - 60.600	194.88 - 198.81	0.59	-	0.59	20
6-1907114-1	60.390 - 61.610	198.12 - 202.13	0.59	-	0.59	20
6-1907114-2	61.380 - 62.620	201.37 - 205.44	0.59	-	0.59	20
6-1907114-3	62.370 - 63.630	204.62 - 208.75	0.59	-	0.59	20
6-1907114-4	63.360 - 64.640	207.87 - 212.07	0.6	-	0.6	20
6-1907114-5	64.350 - 65.650	211.12 - 215.38	0.6	-	0.6	20
6-1907114-6	65.340 - 66.660	214.37 - 218.70	0.6	-	0.6	20
6-1907114-7	66.330 - 67.670	217.61 - 222.01	0.6	-	0.6	20
6-1907114-8	67.320 - 68.680	220.86 - 225.32	0.6	-	0.6	20
6-1907114-9	68.310 - 69.690	224.11 - 228.64	0.6	-	0.6	20
7-1907114-0	69.300 - 70.700	227.36 - 231.95	0.61	-	0.61	20
7-1907114-1	70.290 - 71.710	230.61 - 235.26	0.61	-	0.61	20
7-1907114-2	71.280 - 72.720	233.85 - 238.58	0.61	-	0.61	20
7-1907114-3	72.270 - 73.730	237.10 - 241.89	0.61	-	0.61	20
7-1907114-4	73.260 - 74.740	240.35 - 245.20	0.61	-	0.61	20
7-1907114-5	74.250 - 75.750	243.60 - 248.52	0.61	-	0.61	20
7-1907114-6	75.240 - 76.760	246.85 - 251.83	0.61	-	0.61	20
7-1907114-7	76.230 - 77.770	250.09 - 255.15	0.62	-	0.62	20
7-1907114-8	77.220 - 78.780	253.34 - 258.46	0.62	-	0.62	20
7-1907114-9	78.210 - 79.790	256.59 - 261.77	0.62	-	0.62	20
8-1907114-0	79.200 - 80.800	259.84 - 265.09	0.62	-	0.62	20

A	Rev	Per	EC#	RELEASE	3/21/2007	-	JD
P	LTR			REVISION RECORD	DATE	DN	APVD



Restricted To:

DIN Cable Assy Configurator		MATERIAL	HEAT TREAT
OK	Joe Davis		
APVD	Joe Davis	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)			
SCALE	SIZE	DRAWING NO	SHEET
NTS	A2	C-1907114	3 of 4
			REV A

8 7 6 5 4 3 2 1

D
C
B
A

Label 1

Per specification 107-1645-1




Trace # - Bar Code
 Trace # - Human Readable
 Part Number
 Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1



Trace # - Bar Code
 Trace # - Human Readable
 Part Number
 Country of Origin


This label is used on all lengths on this drawing.

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION AND IS TO BE USED ONLY FOR THE PURPOSES SPECIFIED HEREIN. IT MAY NOT BE DISCLOSED TO ANY OTHER PERSONS OR ORGANIZATIONS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
 CE
 DIST
 16

	A	Rev Per EC#	RELEASE	3/21/2007	-	JD		
P	LTR	REVISION RECORD		DATE	DIN	APVD		



DIMENSIONS:
 meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLC ± .
 1 PLC ± .
 2 PLC ± .
 3 PLC ± .
 4 PLC ± .

Restricted To:

DIN	Cable Assy Configurator	MATERIAL	-	HEAT TREAT	-
CHK	Joe Davis				
APVD	Joe Davis				
NAME	FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)				
SCALE	NTS	SIZE	A2	DRAWING NO	C- 1907114
SHEET	4 of 4	REV	A		

D
C
B
A